

Thermostatic Mixing Valve Series 410 - TH

Unit No. 74146 (3/4")

Includes thermometer

Inlets & Outlet are 3/4" NPT


The master controller shall be of the thermostatic type with liquid filled motor. The controller shall maintain the set point temperature during periods of fluctuating inlet pressures and temperatures. Valve construction will include a bronze body and replaceable corrosion resistant components. The piston and liner are stainless steel. The mixing valve shall employ an adjustable set point range and high temperature limit stop. Each unit will be equipped with stop and check valves for each inlet.

Includes 0-200° F dial thermometer.

DIMENSIONS:

Valve Number	A	B	C
410	9 1/2"	9 1/2"	5 1/2"

FLOW CAPACITIES SINGLE STAGE - SERIES 410



FINISH

- Plain Bronze
- Chrome Plate
- Other

TEMP. RANGE

- 50° to 100° F
- 85° to 135° F
- 100° to 150° F
- Special _____

SET POINT

- 80° F
- 110° F
- 130° F

CAPACITIES - MODEL 410

Pressure Drop PSI	5	10	20	30	45	60
Valve Number	Capacity					
410-GPM	5	8	12	15	20	24
410-LPM	19	30	45	56	75	91



MANUFACTURING CO., INC.

5330 East 25th Street
 Indianapolis, Indiana 46218
 Phone (317) 261-1212
 Fax (317) 261-1208

Specification subject to change without notice.