



RSUB-2-A

**A.G.A. CERTIFIED RATINGS & CAPACITIES**

<b>Fuel Type</b>	Natural/Propane Gas	<b>Boiler FLA</b>	1*
<b>Input BTU/hr.</b>	150,000 / 44 kW	<b>Min. Gas Pressure Required</b>	5" W.C.**
<b>Output BTU/hr.</b>	123,000 / 36 kW	<b>Max. Gas Pressure Allowed</b>	14" W.C.
<b>Electrical Requirements</b>	120VAC / 1 ph / 60 hz	<b>Operating Weight</b>	171 lbs. / 77 kg.

**TEMPERATURE RISE / PRESSURE DROP**

10° F / 5.5° C			
Flow Rate		Pressure Drop	
GPM	L/s	Ft	kPa
24.6	1.6	0.13	0.4
<b>2 Pass</b>			
24.6	1.6	0.94	2.8
<b>4 Pass</b>			

**BOILER TRIM & CONTROLS**

<b>Gas Valve - CON</b>	Honeywell VR8300A 1/2"	<b>Ignition Control</b>	Honeywell S8610M
<b>Gas Valve - INT</b>	Honeywell VR8304M 1/2"	<b>Relief Valve - SW</b>	3/4" x 3/4" set @ 125 psi
<b>Gas Valve</b>	Honeywell VR8304Q 3/4" - 2 Stg.	<b>Relief Valve - SB</b>	3/4" x 3/4" set @ 30 psi
<b>Operating Control (SB)</b>	Jumo - Std Pilot/On/Off	<b>High Limit (SB)</b>	Jumo
<b>Operating Control (SW)</b>	Jumo - Std Pilot/On/Off	<b>High Limit (SW)</b>	Jumo
<b>Operating Control (SB/SW)</b>	Honeywell L6008G - 2 Stage		

**RECOVERY CAPACITY**

40°F	22° C	60°F	33° C	80°F	44° C	100°F	56° C	120°F	67° C	140°F	78° C
369	1397	246	932	185	699	148	559	123	466	105	399

**A.S.M.E.**

<b>ASME Sect IV Htg Surface</b>	25.0 Sq. Ft. / 2.32 Sq. M.	<b>Design Data</b>	Max. 160 psig & 250° F
---------------------------------	----------------------------	--------------------	------------------------

**NOTE:** Dimensions are approximate and should not be used to "rough-in" equipment.

\* Add circulator amps.

\*\*For incoming gas pressures lower than 5" W.C. natural or 12" W.C. propane, consult factory.

**REP FIRM** \_\_\_\_\_

**SUBMITTED BY** \_\_\_\_\_

**JOB NAME** \_\_\_\_\_

**ARCHITECT** \_\_\_\_\_

**ENGINEER** \_\_\_\_\_

**CONTRACTOR** \_\_\_\_\_

**DATE** \_\_\_\_\_

# SPECTRUM 150

**Category I Appliance**

Must be vented into a negative pressure vent system.

® A Division of Mestek, Inc.  
Westfield, MA 01085  
(413) 568-9571